

Countdown Timer (CDT) – Numeric (Dual Color)

Name of the Product : Countdown Timer (CDT) – Numeric (Dual Color)

Model No.: EE-CDT-MS For MS Cabinet & EE-CDT-PC for 300mm Polycarbonate Housing

Specification

Technology – Hi-Brite Light Emitting Diode (LED)

CDT Cabinet/Enclosure

Enclosure Material MS/Polycarbonate

Cabinet Color Black

Cabinet Size 490mm x 350mm x 140 mm for MS Cabinet Approx
350mm x 350mm x 245mm for Polycarbonate Housing Approx

Digit Type & Size 2 ½ Dual Numeric Count with 8" Digit Height for MS Cabinet
2 ½ Dual Numeric Count with 6" Digit Height for Polycarbonate Housing

Display Capability 0-199

Display Color Red & Green

Lens Type Clear Lens/Sheet

Mounting Pole Mounted

CDT-LED

Type Hi-Brite, 5mm Water Clear LED

Forward current 20mA Typical

Wave Length -Typical 630 ± 5nm (Red) & 500 ± 5nm (Green)

Luminous Intensity Better than 400cd

Viewing Angle 23° - 30°

Visibility Better than 300 Meters.

Electrical

Sense Input 230V AC or 12V/24V DC

Power Consumption Less than 12Watt

Environmental

Operating Temperature 0° C to +60° C

Humidity 95% RH

Ingress Protection IP 65